



SIZE		0.5	01	02	04	08	16	32
TORQUE [Nm]	Dy.	5	10	20	40	80	160	320
	St.	6	13	25	50	100	200	400
B		25.2	28.6	32.5	35.9	42.2	46	49.8
E		59	74	93	117	150	190	235
D1		59	74	93	117	150	190	235
D2		58	73.5	92	116	147	186	230
D3 H8		42	52	62	80	90	110	140
D4h8		72	92	115	140	180	220	275
D5		30.5	39.5	51.5	66.5	-	-	-
D6		34	43.5	54	70	90	112	140
d2		46	58	74	94	118	150	185
d3		3.1	4.1	5.1	6.3	8.4	10.4	12.4
d4		66	83	104	128	165	205	255
d5		3.2	4.3	5.3	6.4	6.6	9	11
d6		3.5	4	5	6	9	11	14
d7		39	50	62	80	102	128	159
d8		53	67	84	106	135	170	211
h		-	-	-	-	91	111	-
k		0.3	0.4	0.5	0.6	0.8	1	1.2
n		1.5	2	2	2.5	2.5	3	3
s		0.3	0.3	0.3	0.3	0.4	0.4	0.4
u		-	-	-	-	7	8	9
z		2	2.5	2.5	3	-	-	-
POWER [W]	at 20°C	10	12.5	20	25	31	42	55
	at 120°C	7.5	9	15	18	22	30	40
Permitted centre offset mm	Rotor/arm	0.05	0.10	0.10	0.10	0.15	0.15	0.15
	Rotor/mag	0.10	0.10	0.15	0.15	0.15	0.20	0.20
	Arm/arm	0.15	0.15	0.20	0.20	0.20	0.25	0.25
	Arm/mag	0.20	0.25	0.30	0.30	0.35	0.40	0.40

Also available 0.05,0.16, 63 & 125 sizes on request.